

# VELA 600 direct

suspended

073-12515370



Project / Type
Notes
Count / Date



Round luminaire housing in aluminium, rolled profile, seamlessly welded; surface white powder coated; highly reflective coating for improved efficiency; suspended luminaire with 1500mm cable suspension; with integrated tool-less suspension height adjustment; incl. feeder cable; completely homogeneously illuminated, satinised PMMA cover; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 80$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; canopy with 2 cable openings and plug-in terminal for through wiring; degree of protection IP40; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



IP 40	220-240V	X-PERT	X-PERT
-------	----------	--------	--------

### General

Ceiling , Suspended
white , RAL9010 <sup>1</sup>
IP40
4020 lm

### LED

3000 K
CRI $\geq 80$
L90 / 50000 h
photobio. safety RG 0 - no Risk
initial MacAdam $\leq 3$ SDCM
MR 0.54
MDER 0.49

### Optical

Opal
PstLM $\leq 1.0$ <sup>2</sup>
SVM $\leq 0.4$ <sup>2</sup>

### Electrical

DALI-2
31 W
PC1 220-240V
130 lm/W
1 DALI Addr.

### Physical

cable 1500 mm
diameter 600 mm
height 87 mm
5.4 kg

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Installation instructions



## Lighting calculator

