

# VELA 450 direct / indirect power

suspended  
073-144453XK



Project / Type


Notes

Count / Date





Round luminaire housing in aluminium, rolled profile, seamlessly welded; surface special colours powder coated; highly reflective coating for improved efficiency; suspended luminaire with adjustable pendant rod mounting (chrome) 1000mm, feed in rod; microprismatic PMMA cover; completely homogeneous illumination;  $UGR \leq 16$ ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above  $65^\circ \leq 3000 \text{ cd/m}^2$ ; direct / indirect radiation characteristic for additional accentuation of the ceiling; light colour 3000 K; binning initial MacAdam  $\leq 3 \text{ SDCM}$ ; CRI  $\geq 80$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; canopy with 2 cable openings and plug-in terminal for through wiring; degree of protection IP40; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



### General

Ceiling | Suspended

special colours

IP40

indirect 767 lm | direct 1960 lm

total 2730 lm

### LED

3000 K

CRI  $\geq 80$

L90 / 50000 h

initial MacAdam  $\leq 3 \text{ SDCM}$

MR 0.54 | MDER 0.49

### Optical

Microprismatic | microprismatic

$UGR \leq 16 \mid \geq 65^\circ < 3000 \text{ cd/m}^2$

$PstLM \leq 1.0 \mid SVM \leq 0.4 \supset 1$

### Electrical

DALI-2 | 1 DALI Addr.

PC1 | 220-240 V

system 21.1 W

system 129 lm/W <sup>2</sup>

### Physical

rod 1000 mm

diameter 450 mm | height 87 mm

4.1 kg

<sup>1</sup> Value of containing product at full load (undimmed)  
<sup>2</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Installation instructions



## Lighting calculator

