

SONO 600 direct / indirect

surface

071-91585370



Project / Type

Notes

Count / Date



IP 40

220-240V

General

Ceiling / Wall , Surface

white , RAL9010 ¹

IP40

indirect 2850 lm

direct 5830 lm

total 8680 lm

LED

3000 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.54

MDER 0.49

Optical

Opal

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

DALI-2

67 W

PC1 220-240V

130 lm/W

2 DALI Addr.

Physical

diameter 595 mm

height 80 mm

5.7 kg


¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Round luminaire housing in die-cast aluminium; surface white powder coated; suitable for wall or ceiling mounting; time saving installation through snap-in mounting system; LED board highly reflective lacquered for higher efficiency; same luminance for all size versions; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; completely homogeneously illuminated, satin PMMA cover; direct / indirect radiation characteristic for additional accentuation of the ceiling; luminaire with 2 cable openings and plug-in terminal for through wiring; degree of protection IP40; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. DALI-2 converter; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



Product drawing

