

SONO 450 direct / indirect

surface

071-91485170



Project / Type


Notes

Count / Date




Round luminaire housing in die-cast aluminium; surface white powder coated; suitable for wall or ceiling mounting; time saving installation through snap-in mounting system; LED board highly reflective lacquered for higher efficiency; same luminance for all size versions; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; completely homogeneously illuminated, satin PMMA cover; direct / indirect radiation characteristic for additional accentuation of the ceiling; luminaire with 2 cable openings and plug-in terminal for through wiring; degree of protection IP40; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; shock resistance IK07; internal wiring in light halogen free; incl. converter, non dimmable; light source not replaceable; control gear replaceable by an authorized professional;

Light distribution



Product drawing



IP 40

IK 07

220-240V

X-PERT

General

Ceiling / Wall , Surface

white , RAL9010 ¹

IP40

IK07

indirect 1130 lm

direct 3280 lm

total 4410 lm

LED

3000 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.54

MDER 0.49

Optical

Opal

PstLM ≤ 1.0 ²

Electrical

non DIM

34 W

PC1 220-240V

130 lm/W

Physical

diameter 445 mm

height 80 mm

3.8 kg

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions

