

# SONO 350 direct

surface

071-9136637ONL3



Project / Type


Notes

Count / Date




Round luminaire housing in die-cast aluminium; surface pure white powder coated; suitable for wall or ceiling mounting; time saving installation through snap-in mounting system; LED board highly reflective lacquered for higher efficiency; same luminance for all size versions; light colour 4000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 80$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; completely homogeneously illuminated, satin PMMA cover; luminaire with 2 cable openings and plug-in terminal for through wiring; degree of protection IP50; PC1; 220-240 V; shock resistance IK07; internal wiring in light halogen free; incl. DALI-2 converter; incl. LED emergency light element with 3h rechargeable battery and self-test; light source not replaceable; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing



### General

Ceiling / Wall | Surface

pure white | RAL 9010 <sup>1</sup>

IP50

IK07

2210 lm

### LED

4000 K

CRI  $\geq 80$

L90 / 50000 h

initial MacAdam  $\leq 3$  SDCM

MR 0.72 | MDER 0.66

### Optical

Opal | opal (lambertsch)

### Electrical

DALI-2 | 1 DALI Addr.

PC1 | 220-240 V

3h accupack

system 15.9 W

system 139 lm/W <sup>2</sup>

### Physical

diameter 345 mm | height 80 mm

2.9 kg

<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Installation instructions



# SONO 350 direct

surface

071-9136637ONL3



Project / Type

Notes

Count / Date

## Mounting accessories

### DISMOUNTING TOOL

TYPE  
vacuum cup

ARTICLE NUMBER(S)  
086-30000

