

MOVE IN 32 round

trimless


063-8111517F 063-8811117 002-90743



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Semi-Recessed
 white , RAL9016 ¹
 Mounting set traffic white
 IP20
 795 lm

LED

3000 K
 CRI ≥ 90
 L80 / 50000 h
 initial MacAdam ≤ 2 SDCM
 R_g: 100 , R_f: 91 , R_{f(1-15)}: 88
 MR 0.59
 MDER 0.53

Optical

flood
 beam angle 34°
 PstLM ≤ 1.0 ²
 SVM ≤ 0.4 ²

Electrical

DALI-2
 11.7 W
 PC2 220-240V
 68 lm/W
 1 DALI Addr.

Physical


trimless
 diameter 63 mm
 height 92 mm
 0.44 kg

Cutout

diameter 54 mm
 min. ceiling thickness 9 mm
 max. ceiling thickness 25 mm
 recessed depth 110 mm

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



flood 34°

h (m)	E0° (lx)	ø (m)
1	2590	0.61
2	650	1.21
3	290	1.82
4	160	2.42
5	100	3.03

Product drawing



Installation instructions



Lighting calculator



[063-8111517F 063-8811117 002-90743] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.

© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

04.05.2024

1 / 1