

# MOVE IN 32 round

trim

063-8111418M 063-8821117 002-90743



Project / Type

Notes

Count / Date



### General

Ceiling , Semi-Recessed

black , RAL9005 <sup>1</sup>

Mounting set traffic white

IP20

786 lm

### LED

2700 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>(1-15)</sub>: 89

MR 0.53

MDER 0.48

### Optical

medium

beam angle 24°

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

### Electrical

DALI-2

11.6 W

PC2 220-240V

68 lm/W

1 DALI Addr.

### Physical

trim

diameter 65 mm

height 93 mm

0.3 kg

### Cutout

diameter 54 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 140 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

### Light distribution



medium 24°

h (m)	E0° (lx)	ø (m)
1	4180	0.42
2	1040	0.83
3	460	1.25
4	260	1.67
5	170	2.09

### Product drawing



### Installation instructions



### Lighting calculator

