

MOVE IN 32 round

trim

063-8111418M 063-8821117 002-90742



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Semi-Recessed _____

black , RAL9005 ¹ _____

Mounting set traffic white _____

IP20 _____

786 lm _____

LED

2700 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89 _____

MR 0.53 _____

MDER 0.48 _____

Optical

medium _____

beam angle 24° _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

non DIM _____

11.6 W _____

PC2 220-240V _____

68 lm/W _____

Physical

trim _____

diameter 65 mm _____

height 93 mm _____

0.15 kg _____

Cutout

diameter 54 mm _____


min. ceiling thickness 2 mm _____

max. ceiling thickness 25 mm _____

recessed depth 110 mm _____

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



medium 24°

h (m)	E0° (lx)	ø (m)
1	4180	0.42
2	1040	0.83
3	460	1.25
4	260	1.67
5	170	2.09

Product drawing



Installation instructions



Lighting calculator

