

# MOVE IN 32 round

trimless

063-8111418M 063-8811117 002-90742



Project / Type

Notes

Count / Date



## General

Ceiling , Semi-Recessed  
black , RAL 9005 <sup>1</sup>  
IP20  
786 lm  
fixture 90 lm/W<sup>2</sup>

## LED

2700 K  
CRI ≥ 90  
L80 / 50000 h  
initial MacAdam ≤ 2 SDCM  
R<sub>g</sub>: 99 , R<sub>r</sub>: 91 , R<sub>t(1-15)</sub>: 89  
MR 0.53  
MDER 0.48

## Optical

medium  
beam angle 24°  
PstLM ≤ 1.0 <sup>3</sup>  
SVM ≤ 0.4 <sup>3</sup>

## Electrical

non DIM  
220-240 V  
system 11.6 W  
fixture 8.7 W  
36 Vf  
250 mA  
PC2

## Physical

trimless  
diameter 63 mm  
height 92 mm  
0.35 kg

## Cutout

diameter 54 mm  
min. ceiling thickness 9 mm  
max. ceiling thickness 25 mm  
recessed depth 110 mm

<sup>1</sup> RAL code  
<sup>2</sup> incl. consideration of optical losses & internal control unit losses  
<sup>3</sup> Value of containing product at full load (undimmed)

## Light distribution



medium 24°

h (m)	E0° (lx)	ø (m)
1	4180	0.42
2	1040	0.83
3	460	1.25
4	260	1.67
5	170	2.09

## Product drawing



## Installation instructions



## Lighting calculator

