MOVE IN 32 flex round

trim

063-8211417M 063-8821117 002-90743

Project / Type

Notes

Count / Date

Round spotlight element in aluminium; surface white powder coated; installation without tools in mounting set due to patented ball catch system; recessed light with trim traffic white; suitable for ceiling thickness of 2-25 mm; spotlight element height adjustable without tools: flush with the ceiling, or extended 25 mm or 35 mm; 360° rotatable and 90° tiltable; passive cooling of the LEDs through improved heat sink geometry; with COB (Chip on Board) technology for maximum efficiency; no appearance of multiple shadows; light colour 2700 K; binning initial MacAdam ≤ 2 SDCM; CRI ≥ 90; min. 80% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; high quality, aluminium, vapour deposition coated reflector with faceted lens design; precise radiation characteristic with 24° beam; good glare control through recessed light point level; optical attachment available as accessory; accessories are listed separately; degree of protection IP20; PC2; 220-240 V; incl. DALI-2 converter; converter wired secondary side; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



medium 24°

h (m)	E0° (lx)	ø (m)
1	4180	0.42
2	1040	0.83
3	460	1.25
4	260	1.67
5	170	2.09

Product drawing



General

Ceiling | Semi-Recessed
tilt max 90°
rotation 360°
white | RAL 9016 [1]
Mounting set traffic white
IP20
786 lm

LED

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R_g: 99 | R_f: 91 | $R_{f\{1\text{-}15\}}$: 89
MR 0.53 | MDER 0.48

Optical

medium | beam angle 24°
PstLM ≤ 1.0[2 3 4 5]| SVM ≤ 0.4[2 3 4 5]

Electrical

DALI-2 | 1 DALI Addr.
PC2 | 220-240 V
system 11.6 W | fixture 8.7 W
fixture 90 lm/W [6]
36 Vf | 250 mA

Physical

trim
diameter 65 mm | height 93 mm
0.53 kg

Cutout

diameter 54 mm
min. ceiling thickness 2 mm | max. ceiling thickness 25 mm
recessed depth 140 mm

[1] RAL code [2] wallwasher lens BO 32 007-1965760
[3] soft lens BO 32 007-1965960 [4] oval lens BO 32 007-1965860
[5] Value of containing product at full load (undimmed)
[6] incl. consideration of optical losses & internal control unit losses

Installation instructions

Lighting calculator

['063-8211417M 063-8821117 002-90743'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com