

# MOVE IN 32 round

trimless

063-8111417M 063-8811117 002-90743



Project / Type	
Notes	
Count / Date	



## General

Ceiling , Semi-Recessed
white , RAL9016 <sup>1</sup>
Mounting set traffic white
IP20
786 lm

## LED

2700 K
CRI ≥ 90
L80 / 50000 h
initial MacAdam ≤ 2 SDCM
R <sub>g</sub> : 99 , R <sub>r</sub> : 91 , R <sub>t(1-15)</sub> : 89
MR 0.53
MDER 0.48

## Optical

medium
beam angle 24°
PstLM ≤ 1.0 <sup>2</sup>
SVM ≤ 0.4 <sup>2</sup>

## Electrical

DALI-2
11.6 W
PC2 220-240V
68 lm/W
1 DALI Addr.

## Physical


trimless
diameter 63 mm
height 92 mm
0.44 kg

## Cutout

diameter 54 mm
min. ceiling thickness 9 mm
max. ceiling thickness 25 mm
recessed depth 110 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)


## Light distribution



medium 24°

h (m)	E0° (lx)	ø (m)
1	4180	0.42
2	1040	0.83
3	460	1.25
4	260	1.67
5	170	2.09

## Product drawing



## Installation instructions



## Lighting calculator

