

# MOVE IN 45 round

trim

063-8121517M 063-8822118 002-90724



Project / Type

Notes

Count / Date



General

Ceiling , Semi-Recessed

white , RAL9016 <sup>1</sup>

Mounting set jet black

IP20

1270 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 100 , R<sub>f</sub>: 91 , R<sub>f(1-15)</sub>: 88

MR 0.59

MDER 0.53

Optical

medium

beam angle 24°

PstLM ≤ 1.0 <sup>2</sup>

SVM ≤ 0.4 <sup>2</sup>

Electrical

non DIM

15.9 W

PC2 220-240V

80 lm/W

Physical

trim

diameter 77 mm

height 107 mm

0.57 kg

Cutout

diameter 65 mm

min. ceiling thickness 2 mm

max. ceiling thickness 25 mm

recessed depth 200 mm


<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Light distribution



| h (m) | E0° (lx) | ø (m) |
|-------|----------|-------|
| 1     | 6120     | 0.43  |
| 2     | 1530     | 0.86  |
| 3     | 680      | 1.30  |
| 4     | 380      | 1.73  |
| 5     | 240      | 2.16  |

## Product drawing



Installation instructions

Lighting calculator

