

SONIC direct / indirect asymmetric power

free standing centric pole

059-794155XP



Project / Type

Notes

Count / Date



General

Floor , Standing

special colours

IP20

indirect 9840 lm

direct 4260 lm

total 14100 lm

LED

3000 K

CRI \geq 80

L90 / 50000 h

initial MacAdam \leq 3 SDCM

MR 0.54

MDER 0.49

Optical

Microprismatic

microprismatic

UGR \leq 16

PstLM \leq 1.0 ¹

SVM \leq 0.4 ¹

Electrical

touch DIM

220-240 V

system 105 W

system 134 lm/W²

PC1

Physical

centric pole 2050 mm

diameter 500 mm


height 2102 mm

17.7 kg

¹ Value of containing product at full load (undimmed)


² incl. consideration of optical losses, internal control unit losses
& operating device efficiency

Installation instructions



Free standing luminaire with conical luminaire head in die-cast aluminium; round pedestal with recess for table stand; round aluminium upright tube aligned centre; surface special colours powder coated; direct/indirect illumination characteristic; indirect component with special, inclined PCBs for asymmetric radiation characteristic; indirect component covered with clear acrylic glass; direct lighting portion: micro prismatic PMMA cover; perfectly uniform illumination through use of a diffuse polycarbonate-based film; better light dispersion to transparency ratio; UGR \leq 16; light colour 3000 K; binning initial MacAdam \leq 3 SDCM; CRI \geq 80; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; including TOUCH DIM control for individual control of the brightness; incl. connection cable (3m) with safety plug; sound absorbing accessories available: acoustic elements made of high quality, self-supporting, at least 50 % recycled PET felt (high acoustic performance by doubling the material) or as an acoustically effective lampshade (large selection of colours) with sound absorbing properties; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing

