

# MOVE IN 32 round

trimless

063-8111518S 063-8811117 002-90743



Project / Type

Notes

Count / Date



### General

Ceiling | Semi-Recessed

jet black | RAL 9005

Mounting set traffic white

IP20

817 lm

### LED

3000 K

CRI ≥ 90

L80 / 50000 h

initial MacAdam ≤ 2 SDCM

R<sub>g</sub>: 99 | R<sub>f</sub>: 90 | R<sub>t(1-15)</sub>: 87

MR 0.6 | MDER 0.54

### Optical

spot | beam angle 18°

PstLM ≤ 1.0<sup>1 2 3 4</sup> | SVM ≤ 0.4<sup>1 2 3 4</sup>

### Electrical

DALI-2 | 1 DALI Addr.

PC2 | 220-240 V

system 11.6 W | fixture 8.7 W

fixture 94 lm/W<sup>5</sup>

36 Vf | 250 mA

### Physical

trimless

diameter 63 mm | height 92 mm

0.5 kg


### Cutout

diameter 54 mm

min. ceiling thickness 9 mm | max. ceiling thickness 25 mm

recessed depth 110 mm


### Light distribution



spot 18°

h (m)	E0° (lx)	ø (m)
1	6190	0.32
2	1550	0.63
3	690	0.95
4	390	1.27
5	250	1.58

### Product drawing



<sup>1</sup> oval lens BO 32 007-1965860 <sup>2</sup> soft lens BO 32 007-1965960  
<sup>3</sup> wallwasher lens BO 32 007-1965760  
<sup>4</sup> Value of containing product at full load (undimmed)  
<sup>5</sup> incl. consideration of optical losses & internal control unit losses

### Installation instructions



### Lighting calculator

