

MOVE IN 32 round

trimless

063-8111518S 063-8811117 002-90743



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling , Semi-Recessed _____

black , RAL9005 ¹ _____

Mounting set traffic white _____

IP20 _____

800 lm _____

LED

3000 K _____

CRI ≥ 90 _____

L80 / 50000 h _____

initial MacAdam ≤ 2 SDCM _____

R_g: 100 , R_f: 91 , R₍₁₋₁₅₎: 88 _____

MR 0.59 _____

MDER 0.53 _____

Optical

spot _____

beam angle 18° _____

PstLM ≤ 1.0 ² _____

SVM ≤ 0.4 ² _____

Electrical

DALI-2 _____

11.7 W _____

PC2 220-240V _____

68 lm/W _____

1 DALI Addr. _____

Physical

trimless _____

diameter 63 mm _____

height 92 mm _____

0.45 kg _____

Cutout

diameter 54 mm _____

min. ceiling thickness 9 mm _____

max. ceiling thickness 25 mm _____

recessed depth 110 mm _____

¹ RAL code ² Value of containing product at full load (undimmed)

Light distribution



spot 18°

h (m)	E0° (lx)	ø (m)
1	6060	0.32
2	1510	0.63
3	670	0.95
4	380	1.27
5	240	1.58

Product drawing



Installation instructions



Lighting calculator

