

TASK ACOUSTIC 1200 half square


suspended
059-579226L



Project / Type

Notes

Count / Date



General

Ceiling | Suspended

black

Physical

panel only

length 1155 mm | width 573 mm | height 30 mm

Acoustics

Alpha w (α_w) up to 0.95¹

SAC (sound absorption class) up to A¹

NRC up to 0.95¹

SAA up to 0.91¹

¹ Acoustic data calculations based on TASK ACOUSTIC 1200 half square, cavity 20cm

Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; rectangular design; high quality visual and tactile surface, black; colour may deviate; direct sound is absorbed by the front-mounted fleece, sound reflected from the ceiling/wall by an additional, rear-mounted fleece; this creates high acoustic performance; pendant fitting with 1500mm cable suspension; toolless suspension height adjustment of the acoustic element;

Product drawing



TASK ACOUSTIC 1200 half square

suspended
059-579226L



Project / Type

Notes

Count / Date

Equivalent sound absorption area (A_{eq})

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.43	0.4	0.73	0.97	1.1	1.2

Sound absorption coefficient (α_p)

