

TASK ACOUSTIC 1200 square

suspended
059-579216W



Project / Type

Notes

Count / Date



General

Ceiling | Suspended

white

Physical

panel only

length 1155 mm | width 1155 mm | height 30 mm

Acoustics

Alpha w (α_w) up to 0.95¹

SAC (sound absorption class) up to A¹

NRC up to 0.95¹

SAA up to 0.91¹


¹ Acoustic data calculations based on TASK ACOUSTIC 1200 half square, cavity 20cm

Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; square design; high quality visual and tactile surface, white; colour may deviate; direct sound is absorbed by the front-mounted fleece, sound reflected from the ceiling/wall by an additional, rear-mounted fleece; this creates high acoustic performance; pendant fitting with 1500mm cable suspension; toolless suspension height adjustment of the acoustic element;

Product drawing



TASK ACOUSTIC 1200 square

suspended
059-579216W



Project / Type

Notes

Count / Date

Equivalent sound absorption area (A_{eq})

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.73	1	1.53	1.9	2.2	2.4

Sound absorption coefficient (α_p)

