

TASK ACOUSTIC 1200 square wide


surface
059-579166G



Project / Type

Notes

Count / Date



General

Ceiling | Surface

felt grey

fire resistance class: B-s1, d0

Physical

panel only

length 1155 mm | width 1180 mm | height 30 mm

Acoustics

Alpha w (α_w) up to 0.6 ¹

SAC (sound absorption class) up to C ¹

NRC up to 0.75 ¹

SAA up to 0.76 ¹

¹ Acoustic data calculations based on TASK ACOUSTIC 1200 half square, cavity 3cm

Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; square design; high quality visual and tactile surface, felt grey; colour may deviate; direct sound is absorbed by the front-mounted fleece, sound reflected from the ceiling/wall by an additional, rear-mounted fleece; this creates high acoustic performance; for wall-/ceiling surface mounting;

Product drawing



TASK ACOUSTIC 1200 square wide

surface
059-579166G



Project / Type

Notes

Count / Date

Equivalent sound absorption area (A_{eq})

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.07	0.41	0.95	1.36	1.36	1.36

Sound absorption coefficient (α_p)

