

TASK ACOUSTIC 900 square

surface
059-579115W



Project / Type _____

Notes _____

Count / Date _____



General

Ceiling | Surface _____
white _____

Physical

panel only _____
length 900 mm | width 900 mm | height 30 mm _____

Acoustics

Alpha w (α_w) up to 0.6 ¹ _____
SAC (sound absorption class) up to C ¹ _____
NRC up to 0.75 ¹ _____
SAA up to 0.76 ¹ _____


¹ Acoustic data calculations based on TASK ACOUSTIC 1200 half square, cavity 3cm

Installation instructions



Acoustic element made of high quality, self-supporting PET felt with sound absorbing properties, consisting of at least 50 % post-consumer recycled PET; square design; high quality visual and tactile surface, white; colour may deviate; direct sound is absorbed by the front-mounted fleece, sound reflected from the ceiling/wall by an additional, rear-mounted fleece; this creates high acoustic performance; for wall-/ceiling surface mounting;

Product drawing



TASK ACOUSTIC 900 square

surface
059-579115W



Project / Type _____

Notes _____

Count / Date _____

Equivalent sound absorption area (A_{eq})

125 HZ	250 HZ	500 HZ	1000 HZ	2000 HZ	4000 HZ
0.04	0.24	0.57	0.81	0.81	0.81

Sound absorption coefficient (a_p)

