

**TASK S** direct / indirect  
power  
suspended  
059-5264D37K



Project / Type \_\_\_\_\_

Notes \_\_\_\_\_

Count / Date \_\_\_\_\_



**General**

Ceiling , Suspended \_\_\_\_\_

white , RAL 9010 <sup>1</sup> \_\_\_\_\_

IP20 \_\_\_\_\_

indirect 1490 lm \_\_\_\_\_

direct 2700 lm \_\_\_\_\_

total 4190 lm \_\_\_\_\_

**LED**

tunable white \_\_\_\_\_

2700 K - 6500 K \_\_\_\_\_

CRI ≥ 80 \_\_\_\_\_

L85 / 50000 h \_\_\_\_\_

MR 1.01 \_\_\_\_\_

MDER 0.92 \_\_\_\_\_

**Optical**

Microprismatic \_\_\_\_\_

microprismatic \_\_\_\_\_

UGR ≤ 16 , ≥65° <3000 cd/m<sup>2</sup> \_\_\_\_\_

PstLM ≤ 1.0 <sup>2</sup> \_\_\_\_\_

SVM ≤ 0.4 <sup>2</sup> \_\_\_\_\_

Rectangular luminaire housing with rounded edges in aluminium; extremely flat (only 15mm) and slim (only 180mm) design; modern shape in an elegant design for high demands; surface white powder coated; suspended luminaire with 1500mm cable suspension; with integrated toolless suspension height adjustment on the luminaire; incl. feed (white); direct light distribution through LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; microprismatic PMMA cover; completely homogeneous illumination; same light density for all surface lights with the same components; UGR ≤ 16; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m<sup>2</sup>; light colour: tunable white diodes (2700-6500 K); CRI ≥ 80; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; canopy with 2 cable openings and plug-in terminal for through wiring; degree of protection IP20; PC1; 220-240 V; internal wiring in light halogen free; incl. DALI-2 / DT8 converter; sound absorbing accessories available; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

**Electrical**

DALI-2 DT8 \_\_\_\_\_

220-240 V \_\_\_\_\_

system 36 W \_\_\_\_\_

system 116 lm/W<sup>3</sup> \_\_\_\_\_

PC1 \_\_\_\_\_

1 DALI Addr. \_\_\_\_\_

**Physical**

cable 1500 mm \_\_\_\_\_


length 1180 mm \_\_\_\_\_

width 180 mm \_\_\_\_\_


height 34 mm \_\_\_\_\_

3.5 kg \_\_\_\_\_

**Light distribution**



**Product drawing**



<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)  
<sup>3</sup> incl. consideration of optical losses, internal control unit losses  
& operating device efficiency

**Installation  
instructions**



**Lighting  
calculator**

