

# TASK S direct / indirect soft

suspended

059-525813XK



Project / Type
Notes
Count / Date



## General

Ceiling , Suspended
special colours
IP20
indirect 695 lm
direct 4050 lm
total 4750 lm

## LED

4000 K
CRI $\geq 90$
L90 / 50000 h
initial MacAdam $\leq 3$ SDCM
R <sub>g</sub> : 96 , R <sub>f</sub> : 90 , R <sub>t(1-15)</sub> : 87
MR 0.75
MDER 0.68

## Optical

Microprismatic
microprismatic
UGR $\leq 19$ , $\geq 65^\circ$ <3000 cd/m <sup>2</sup>
PstLM $\leq 1.0$ <sup>1</sup>
SVM $\leq 0.4$ <sup>1</sup>

## Electrical


DALI-2
220-240 V
system 39 W
system 122 lm/W <sup>2</sup>
PC1
1 DALI Addr.

## Physical

cable 1500 mm
length 2315 mm
width 180 mm
height 34 mm
6.5 kg

<sup>1</sup> Value of containing product at full load (undimmed)  
<sup>2</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Light distribution



## Product drawing



## Installation instructions



## Lighting calculator

