

TASK 450 square direct / indirect power


suspended
059-2231138K



Project / Type

Notes

Count / Date



General

Ceiling , Suspended

black , RAL9005 ¹

IP20

indirect 1570 lm

direct 3100 lm

total 4670 lm

LED

4000 K

CRI ≥ 90

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

R_g: 96 , R_r: 90 , R_{t(1-15)}: 87

MR 0.75

MDER 0.68

Optical

Microprismatic


UGR < 19

P_{stLM} ≤ 1.0 ²


SVM ≤ 0.4 ²

square luminaire housing with rounded edges in aluminium; extremely flat design (only 15mm); modern shape in an elegant design for high demands; surface black powder coated; suspended luminaire with 1500mm cable suspension (4 cables); with integrated tool-less suspension height adjustment; incl. feeder cable; direct light distribution through LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; microprismatic PMMA cover; completely homogeneous illumination; same light density for all surface lights with the same components; UGR ≤ 19; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; canopy with 2 cable openings and plug-in terminal for through wiring; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. DALI-2 converter; sound absorbing accessories available; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Electrical

DALI-2

35 W

PC1 220-240V

133 lm/W

1 DALI Addr.

Physical

length 450 mm

width 450 mm

height 41 mm

4.2 kg

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator



TASK 450 square direct / indirect power

suspended
059-2231138K



Project / Type

Notes

Count / Date

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF | 0.98 | 0.97 | 0.95 | 0.93 | 0.92 |
| LSF | 1 | 1 | 1 | 1 | 1 |
| MF | LMF × RSMF × LLMF × LSF | | RSMF ^a | Room Surface Maintenance Factor | |
| MF | Maintenance Factor | | LLMF | Lamp Lumens Maintenance Factor | |
| LMF ^a | Luminaire Maintenance Factor | | LSF | Lamp Survival Faktor | |

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10 | 9 |
| B13 | 13 |
| B16 | 15 |
| B20 | 18 |
| C10 | 18 |
| C13 | 26 |
| C16 | 30 |
| C20 | 36 |

Acoustic accessories

TASK ACOUSTIC inlay TASK angular suspended

| COLOUR | L·W·H (MM) | ARTICLE NUMBER(S) |
|--------------------------|--------------|-------------------|
| marble grey | 1155-1155-30 | 059-579716D |
| felt grey | 1155-1155-30 | 059-579716G |
| black | 1155-1155-30 | 059-579716L |
| white | 1155-1155-30 | 059-579716W |
| acoustic special colours | 1155-1155-30 | 059-579716X |

