

TASK sensor direct / indirect soft

free standing T-shape

059-295317XZ



Project / Type

Notes

Count / Date



General

Floor , Standing

special colours

IP20

indirect 3560 lm

direct 4370 lm

total 7930 lm

LED

4000 K

CRI ≥ 90

L90 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 96 , R_f: 90 , R₍₁₋₁₅₎: 87

MR 0.75

MDER 0.68

Optical

Microprismatic

microprismatic

UGR ≤ 19

PstLM ≤ 1.0 ¹

SVM ≤ 0.4 ¹

Electrical

ESSENTIAL sensor (brightness & presence)

220-240 V

system 71 W

system 112 lm/W²

PC1

Physical

T-shape

length 800 mm

width 320 mm

height 1920 mm

¹ Value of containing product at full load (undimmed)


² incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Free standing luminaire with rectangular head with rounded edges in aluminium; extremely flat design (only 15mm); rectangular aluminium tube support; base stand with recess for table stand (T-shape); modern shape in elegant design for discerning requirements; surface special colours powder coated; direct/indirect light distribution by LGP body (Light Guiding Prism); side coupled light, directed up and down by laser engraving; microprismatic PMMA cover; completely homogeneous illumination; UGR ≤ 19 ; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; luminaire with integrated infrared presence and brightness sensor (ESSENTIAL sensor); automatic light control for individually adjustable brightness; variable automatic shutdown; including TOUCH DIM control for individual control of the brightness; presence sensor detection range $\varnothing 4,5$ m on the floor; incl. connection cable (3m) with safety plug; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing

