

LINEA opal / 1 spot

wall

058-6178647BH



Project / Type _____

Notes _____

Count / Date _____



General

Wall , Surface _____

tilt max 89° _____

white , RAL9010 ¹ _____

IP20 _____

141 lm _____

LED

3000 K²-4000 K³ _____

CRI ≥ 90 _____

L80 / 50000 h²-L85 / 50000 h³ _____

photobio. safety RG 0 - no Risk _____

initial MacAdam ≤ 3 SDCM _____

R_g: 98 , R_f: 90 , R₍₁₋₁₅₎: 88 _____

MR 0.76 _____

MDER 0.69 _____

Optical

Flood _____

beam angle 23° _____

PstLM ≤ 1.0 ⁴ _____

SVM ≤ 0.4 ⁴ _____

High Performance Opal _____

Electrical

DALI-2 / switch (only spotlights) _____


2.2²-70³ W _____

PC1 220-240V _____

64²-110³ lm/W _____


1 DALI Addr. _____

Light distribution



	flood 23°	Spot
h (m)	E0° (lx)	ø (m)
1	584	0.41
2	146	0.83
3	65	1.24
4	37	1.65
5	23	2.07

Product drawing



Physical

length 2510 mm _____

width 40 mm _____

height 100 mm _____

left _____

¹ RAL code ² Spot ³ Linear
⁴ Value of containing product at full load (undimmed)

Installation instructions

