

# TASK long circle direct / indirect power

suspended


059-5282138K



Project / Type


Notes

Count / Date



Ring-shaped suspended luminaire, consisting of single elements in quarter circle or rectangular shape; luminaire housing with rounded edges in aluminium; extremely flat design (only 15mm); modern shape in elegant design for discerning requirements; surface black powder coated; luminaire with 1500 mm cable suspension; with integrated tool-less suspension height adjustment; incl. feeder cable; direct light distribution through LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; microprismatic PMMA cover; completely homogeneous illumination; light colour 4000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 90$ ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; canopy with 2 cable openings and plug-in terminal for through wiring; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. DALI-2 converter; sound absorbing accessories available; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Product drawing



### General

Ceiling , Suspended  
black , RAL9005 <sup>1</sup>  
IP20

### LED

4000 K  
CRI  $\geq 90$   
photobio. safety RG 0 - no Risk  
initial MacAdam  $\leq 3$  SDCM  
 $R_g: 96, R_f: 90, R_{t(1-15)}: 87$   
MR 0.75  
MDER 0.68

### Optical

Microprismatic  
 $P_{stLM} \leq 1.0$  <sup>2</sup>  
 $SVM \leq 0.4$  <sup>2</sup>

### Electrical

DALI-2  
PC1 220-240V  
6 DALI Addr.

### Physical

cable 1500 mm  
length 2725 mm  
width 1535 mm  
height 36 mm

<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Installation instructions

