

# LINEA opal / 1 spot

wall

058-6178637BH



Project / Type

Notes

Count / Date



## General

Wall , Surface

white , RAL9010 <sup>1</sup>

3200 lm/m

IP20

indirect 3850 lm

direct 3850 lm

total 7700 lm

tilt max 89°

172 lm

## LED

3000 K<sup>2</sup>-4000 K<sup>3</sup>

CRI ≥ 97<sup>2</sup>-90<sup>3</sup>

L95 / 50000 h<sup>2</sup>-L85 / 50000 h<sup>3</sup>

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 92<sup>2</sup>-98<sup>3</sup> , R<sub>r</sub>: 86<sup>2</sup>-90<sup>3</sup> , R<sub>(1-15)</sub>: 94<sup>2</sup>-88<sup>3</sup>

MR 0.53<sup>2</sup>-0.76<sup>3</sup>

MDER 0.48<sup>2</sup>-0.69<sup>3</sup>

## Optical

High Performance Opal

PstLM ≤ 1.0 <sup>4</sup>

SVM ≤ 0.4 <sup>4</sup>

Flood

beam angle 30°

## Electrical

DALI-2

2.7<sup>2</sup>-70<sup>3</sup> W

PC1 220-240V

64<sup>2</sup>-110<sup>3</sup> lm/W

1 DALI Addr.

29 W/m

## Physical

length 2510 mm

width 40 mm

height 100 mm

left

<sup>1</sup> RAL code <sup>2</sup> Spot <sup>3</sup> Linear


<sup>4</sup> Value of containing product at full load (undimmed)

## Installation instructions



Light fitting and front cover made of extruded aluminium profile; angular design; no visible screws; surface white powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct and indirect light component: HPO (High Performance Opal) cover for uniform illumination; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; JUST 26 spotlight module 2,6 W / 159 lm / 3000 K left; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution




flood 30°

Spot

h (m)	E0° (lx)	ø (m)
1	419	0.54
2	105	1.09
3	47	1.63
4	26	2.17
5	17	2.72

## Product drawing



[058-6178637BH] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

07.05.2024