


TASK circle direct / indirect
power
suspended
059-5281137K



Project / Type _____

Notes _____

Count / Date _____



General
Ceiling , Suspended
white , RAL9010 ¹
IP20
indirect 6870 lm
direct 13200 lm
total 20100 lm

LED
4000 K
CRI ≥ 90
L90 / 50000 h
photobio. safety RG 0 - no Risk
initial MacAdam ≤ 3 SDCM
R _g : 96 , R _r : 90 , R _{t(1-15)} : 87
MR 0.75
MDER 0.68


Optical
Microprismatic
UGR < 19
P _{stLM} ≤ 1.0 ²
SVM ≤ 0.4 ²

Ring-shaped suspended luminaire, consisting of single elements in quarter circle shape; luminaire housing with rounded edges in aluminium; extremely flat design (only 15mm); modern shape in elegant design for discerning requirements; surface white powder coated; luminaire with 1500 mm cable suspension; with integrated tool-less suspension height adjustment; incl. feeder cable; direct light distribution through LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; light control via highly reflective reflector material; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; microprismatic PMMA cover; completely homogeneous illumination; UGR ≤ 19; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; canopy with 2 cable openings and plug-in terminal for through wiring; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. DALI-2 converter; sound absorbing accessories available; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Electrical
DALI-2
169 W
PC1 220-240V
119 lm/W
4 DALI Addr.

Physical
cable 1500 mm
diameter 1535 mm
height 36 mm

Light distribution



Product drawing



¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

