

# TASK S direct / indirect power

suspended

059-5268D3XK



Project / Type

Notes

Count / Date



## General

Ceiling , Suspended

special colours

IP20

indirect 2970 lm

direct 5410 lm

total 8380 lm

## LED

tunable white

2700 K - 6500 K

CRI  $\geq 80$

L85 / 50000 h

MR 1.01

MDER 0.92

## Optical

Microprismatic

microprismatic

UGR  $\leq 16$ ,  $\geq 65^\circ$  <3000 cd/m<sup>2</sup>

PstLM  $\leq 1.0$ <sup>1</sup>

SVM  $\leq 0.4$ <sup>1</sup>

## Electrical

DALI-2 DT8

220-240 V

system 71 W

system 118 lm/W<sup>2</sup>

PC1

2 DALI Addr.

## Physical

cable 1500 mm

length 2315 mm

width 180 mm


height 34 mm

7.2 kg

<sup>1</sup> Value of containing product at full load (undimmed)

<sup>2</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Light distribution



## Product drawing



['059-5268D3XK'] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.  
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

30.04.2025