

LINEA opal / asymmetric

wall

058-6178618AA



Project / Type


Notes

Count / Date



Light fitting and front cover made of extruded aluminium profile; angular design; no visible screws; surface black powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct light component: HPO (High Performance Opal) cover for uniform illumination; indirect light component: with specially computed, asymmetrical lens for homogeneous lighting intensity (installation optionally for floor or ceiling illumination); light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Wall Surface
black RAL 9005 ¹
IP20
indirect 4620 lm direct 3890 lm
total 8510 lm
3540 lm/m

LED

4000 K
CRI ≥ 90
L85 / 50000 h
initial MacAdam ≤ 3 SDCM
R _g : 98 R _f : 90 R _{f(1-15)} : 88
MR 0.76 MDER 0.69

Optical

High Performance Opal / Asymmetric asymmetric
PstLM ≤ 1.0 ² SVM ≤ 0.4 ²

Electrical

non DIM
PC1 220-240 V
system 71 W
system 120 lm/W ³
29 W/m

Physical

length 2410 mm width 40 mm height 100 mm
5.9 kg

¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

