

LINEA opal / 1 spot

wall

058-6178548CH



Project / Type

Notes

Count / Date



General

Wall , Surface

tilt max 89°

black , RAL 9005 ¹

IP20

141 lm

LED

3000 K

CRI ≥ 90

L80 / 50000 h²-L85 / 50000 h³

initial MacAdam ≤ 3 SDCM

R_g: 100²-99³ , R_f: 91 , R_{1-15}: 88²-89³

MR 0.59²-0.61³

MDER 0.53²-0.55³

Optical

flood²-opal (lambertsch)³

beam angle 23°


PstLM ≤ 1.0² ³ ⁴

SVM ≤ 0.4² ³ ⁴

High Performance Opal


Light fitting and front cover made of extruded aluminium profile; angular design; no visible screws; surface black powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct and indirect light component: HPO (High Performance Opal) cover for uniform illumination; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; JUST 26 spotlight module 2,2 W / 141 lm / 3000 K right, incl. switch; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



flood 23°		Spot	
h (m)	E0° (lx)	ø (m)	
1	584	0.41	
2	146	0.83	
3	65	1.24	
4	37	1.65	
5	23	2.07	

Product drawing



Electrical

DALI-2 / switch (only spotlights)

220-240 V

system 2.2²-70³ W

system 64²-100³ lm/W⁵

PC1

1 DALI Addr.

Physical

length 2510 mm

width 40 mm

height 100 mm

right

¹ RAL code ² Spot ³ Linear
⁴ Value of containing product at full load (undimmed)
⁵ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

