

LINEA opal / 2 spots

wall

058-6178538DH



Project / Type _____


Notes _____

Count / Date _____



Light fitting and front cover made of extruded aluminium profile; angular design; no visible screws; surface black powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct and indirect light component: HPO (High Performance Opal) cover for uniform illumination; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97 ; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; 2x JUST 26 spotlight module 2,6 W / 159 lm / 3000 K (1x left, 1x right); incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



flood 30° Spot

h (m)	E0° (lx)	ø (m)
1	419	0.54
2	105	1.09
3	47	1.63
4	26	2.17
5	17	2.72

Product drawing



General

Wall , Surface
black , RAL9005 ¹
2900 lm/m
IP20
indirect 3490 lm
direct 3490 lm
total 6980 lm
tilt max 89°
344 lm

LED

3000 K
CRI $\geq 97^{2-90^3}$
L95 / 50000 h²-L85 / 50000 h³
photobio. safety RG 0 - no Risk
initial MacAdam ≤ 3 SDCM
R_g: 92²-99³, R_r: 86²-91³, R₍₁₋₁₅₎: 94²-89³
MR 0.53²-0.61³
MDER 0.48²-0.55³

Optical

High Performance Opal
PstLM ≤ 1.0 ⁴
SVM ≤ 0.4 ⁴
Flood
beam angle 30°

Electrical

DALI-2
5.4²-70³ W
PC1 220-240V
64²-100³ lm/W
2²-1³ DALI Addr.
29 W/m

Physical

length 2610 mm
width 40 mm
height 100 mm

¹ RAL code ² Spot ³ Linear
⁴ Value of containing product at full load (undimmed)

Installation instructions

