

# LINEA opal / 2 spots

wall

058-6178537DH



Project / Type


Notes

Count / Date




Light fitting and front cover made of extruded aluminium profile; angular design; no visible screws; surface white powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct and indirect light component: HPO (High Performance Opal) cover for uniform illumination; light colour 3000 K; binning initial MacAdam  $\leq 3$  SDCM; CRI  $\geq 97$ ; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; 2x JUST 26 spotlight module 2,6 W / 159 lm / 3000 K (1x left, 1x right); incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



flood 30°		Spot	
h (m)	E0° (lx)	ø (m)	
1	419	0.54	
2	105	1.09	
3	47	1.63	
4	26	2.17	
5	17	2.72	

## Product drawing



## General

Wall | Surface

tilt max 89°

white | RAL 9010 <sup>1</sup>

IP20

344 lm

## LED

3000 K

CRI  $\geq 97^{2-90^3}$

L95 / 50000 h<sup>2</sup>-L85 / 50000 h<sup>3</sup>

initial MacAdam  $\leq 3$  SDCM

R<sub>g</sub>: 102<sup>2</sup>-99<sup>3</sup> | R<sub>f</sub>: 96<sup>2</sup>-91<sup>3</sup> | R<sub>{f1-15}</sub>: 96<sup>2</sup>-89<sup>3</sup>

MR 0.63<sup>2</sup>-0.61<sup>3</sup> | MDER 0.57<sup>2</sup>-0.55<sup>3</sup>

## Optical

beam angle 30°

PstLM  $\leq 1.0^{2-3-4}$  | SVM  $\leq 0.4^{2-3-4}$

High Performance Opal | flood<sup>2</sup>-opal (lambertsch)<sup>3</sup>

## Electrical

DALI-2 | 2<sup>2</sup>-1<sup>3</sup> DALI Addr.

PC1 | 220-240 V

system 5.4<sup>2</sup>-70<sup>3</sup> W

system 64<sup>2</sup>-100<sup>3</sup> lm/W <sup>5</sup>

## Physical

length 2610 mm | width 40 mm | height 100 mm

6.8 kg

<sup>1</sup> RAL code <sup>2</sup> Spot <sup>3</sup> Linear  
<sup>4</sup> Value of containing product at full load (undimmed)  
<sup>5</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

## Installation instructions

