

LINEA opal / 1 spot

wall

058-6172D47CH



Project / Type _____

Notes _____

Count / Date _____



General

Wall , Surface _____

white , RAL9010 ¹ _____

3330 lm/m _____

IP20 _____

indirect 1010 lm _____

direct 1010 lm _____

total 2020 lm _____

tilt max 89° _____

141 lm _____

LED

3000 K²-tunable white³ _____

2700 K - 5000 K _____

CRI ≥ 90 _____

L80 / 50000 h²-L85 / 50000 h³ _____

photobio. safety RG 0 - no Risk _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 , R_f: 90 , R_{t(1-15)}: 88 _____

MR 0.53 _____

MDER 0.48 _____

Optical

High Performance Opal _____

PstLM ≤ 1.0 ⁴ _____

SVM ≤ 0.4 ⁴ _____

Flood _____

beam angle 23° _____

Electrical

DALI-2 / switch (only spotlights) _____

2.2²-20.9³ W _____

PC1 220-240V _____

64²-97³ lm/W _____

1 DALI Addr. _____

34 W/m _____

Physical

length 710 mm _____

width 40 mm _____


height 100 mm _____

right _____

¹ RAL code ² Spot ³ Linear

⁴ Value of containing product at full load (undimmed)


Light distribution



flood 23° Spot

h (m)	E0° (lx)	ø (m)
1	584	0.41
2	146	0.83
3	65	1.24
4	37	1.65
5	23	2.07

Product drawing



Installation instructions

