

# LINEA opal / 2 spots

wall

058-6174D38DH



Project / Type

Notes

Count / Date



### General

Wall , Surface

tilt max 89°

black , RAL9005 <sup>1</sup>

IP20

344 lm

### LED

3000 K<sup>2</sup>-tunable white<sup>3</sup>

CRI ≥ 97<sup>2</sup>-90<sup>3</sup>

L95 / 50000 h<sup>2</sup>-L85 / 50000 h<sup>3</sup>

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 92<sup>2</sup>-99<sup>3</sup> , R<sub>f</sub>: 86<sup>2</sup>-90<sup>3</sup> , R<sub>(f-15)</sub>: 94<sup>2</sup>-88<sup>3</sup>

MR 0.53

MDER 0.48

2700 K - 5000 K

### Optical

Flood

beam angle 30°

PstLM ≤ 1.0 <sup>4</sup>

SVM ≤ 0.4 <sup>4</sup>

High Performance Opal

### Electrical

DALI-2

5.4<sup>2</sup>-42<sup>3</sup> W

PC1 220-240V

64<sup>2</sup>-96<sup>3</sup> lm/W

2<sup>2</sup>-1<sup>3</sup> DALI Addr.


### Physical

length 1410 mm

width 40 mm


height 100 mm

### Light distribution



flood 30°		Spot
h (m)	E0° (lx)	ø (m)
1	419	0.54
2	105	1.09
3	47	1.63
4	26	2.17
5	17	2.72

### Product drawing



<sup>1</sup> RAL code <sup>2</sup> Spot <sup>3</sup> Linear  
<sup>4</sup> Value of containing product at full load (undimmed)

### Installation instructions

