

# LINEA opal / 1 spot

wall

058-6172D47BH



Project / Type

Notes

Count / Date



### General

Wall , Surface

tilt max 89°

white , RAL 9010 <sup>1</sup>

IP20

141 lm

### LED

3000 K<sup>2</sup>-tunable white<sup>3</sup>

CRI ≥ 90

L80 / 50000 h<sup>2</sup>-L85 / 50000 h<sup>3</sup>

initial MacAdam ≤ 3 SDCM

R<sub>g</sub>: 100<sup>2</sup>-99<sup>3</sup> , R<sub>f</sub>: 91<sup>2</sup>-90<sup>3</sup> , R<sub>f(1-15)</sub>: 88

MR 0.59<sup>2</sup>-0.53<sup>3</sup>

MDER 0.53<sup>2</sup>-0.48<sup>3</sup>

2700 K - 5000 K

### Optical

flood<sup>2</sup>-opal (lambertsch)<sup>3</sup>

beam angle 23°

PstLM ≤ 1.0<sup>2 3 4</sup>

SVM ≤ 0.4<sup>2 3 4</sup>

High Performance Opal

### Electrical

DALI-2 / switch (only spotlights)<sup>2</sup>-DALI-2 DT8 / switch (only spotlights)<sup>3</sup>

220-240 V

system 2.2<sup>2</sup>-20.9<sup>3</sup> W

system 64<sup>2</sup>-97<sup>3</sup> lm/W<sup>5</sup>

PC1

1 DALI Addr.

### Physical

length 710 mm

width 40 mm

height 100 mm


left

<sup>1</sup> RAL code <sup>2</sup> Spot <sup>3</sup> Linear

<sup>4</sup> Value of containing product at full load (undimmed)


<sup>5</sup> incl. consideration of optical losses, internal control unit losses & operating device efficiency

### Light distribution



	flood 23°	Spot
h (m)	E0° (lx)	ø (m)
1	584	0.41
2	146	0.83
3	65	1.24
4	37	1.65
5	23	2.07

### Product drawing



### Installation instructions



# LINEA opal / 1 spot

wall

058-6172D47BH



Project / Type

Notes

Count / Date

## Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.96	0.94	0.91	0.89
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF <sup>a</sup>	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF <sup>a</sup>	Luminaire Maintenance Factor		LSF	Lamp Survival Factor	

<sup>a</sup> According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

## Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	13
B13	16
B16	22
B20	27
C10	21
C13	28
C16	36
C20	45

