

LINEA opal / 1 spot

wall

058-6172D38CH



Project / Type

Notes

Count / Date



General

Wall | Surface

black | RAL 9005¹

IP20

indirect 1010 lm | direct 1010 lm

total 2020 lm

3330 lm/m

tilt max 89°

172 lm

LED

3000 K²-tunable white³ | 2700 K - 5000 K

CRI ≥ 97²-90³

L95 / 50000 h²-L85 / 50000 h³

initial MacAdam ≤ 3 SDCM

R_g: 102²-99³ | R_f: 96²-90³ | R_{f1-15}: 96²-88³

MR 0.63²-0.53³ | MDER 0.57²-0.48³

Optical

High Performance Opal | flood²-opal (lambertsch)³

PstLM ≤ 1.0³ 2 4 | SVM ≤ 0.4³ 2 4

beam angle 30°

Electrical

DALI-2²-DALI-2 DT8³ | 1 DALI Addr.

PC1 | 220-240 V

system 2.7²-20.9³ W

system 64²-97³ lm/W⁵

34 W/m

Physical

length 710 mm | width 40 mm | height 100 mm

2 kg

right

¹ RAL code ² Spot ³ Linear

⁴ Value of containing product at full load (undimmed)


⁵ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Light fitting and front cover made of extruded aluminium profile; angular design; no visible screws; surface black powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct and indirect light component: HPO (High Performance Opal) cover for uniform illumination; light colour: tunable white diodes (2700-5000 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; JUST 26 spotlight module 2,6 W / 159 lm / 3000 K right; incl. DALI-2 / DT8 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



flood 30° Spot

h (m)	E0° (lx)	ø (m)
1	419	0.54
2	105	1.09
3	47	1.63
4	26	2.17
5	17	2.72

Product drawing



[058-6172D38CH] The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the electrical connected load are initially subject to a tolerance of +/- 10%, and those for the colour temperature are initially subject to a tolerance of +/- 150 K. No liability is assumed for typographical or printing errors. The general terms and conditions of XAL GmbH apply.
© XAL GmbH · Auer-Welsbach-Gasse 36 · 8055 Graz · Austria · www.xal.com

26.06.2025

LINEA opal / 1 spot

wall
058-6172D38CH



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.99	0.99	0.99	0.99	0.99
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Factor	

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	80
B13	104
B16	130
B20	162
C10	135
C13	175
C16	220
C20	270

