

LINEA opal / 1 spot

wall

058-6172638CH



Project / Type


Notes

Count / Date




Light fitting and front cover made of extruded aluminium profile; angular design; no visible screws; surface black powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct and indirect light component: HPO (High Performance Opal) cover for uniform illumination; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 97 ; min. 95% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; JUST 26 spotlight module 2,6 W / 159 lm / 3000 K right; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



flood 30°		Spot
h (m)	E0° (lx)	ø (m)
1	419	0.54
2	105	1.09
3	47	1.63
4	26	2.17
5	17	2.72

Product drawing



General

Wall , Surface

black , RAL9005 ¹

3180 lm/m

IP20

indirect 963 lm

direct 963 lm

total 1926 lm

tilt max 89°

172 lm

LED

3000 K²-4000 K³

CRI $\geq 97^{2-90^3}$

L95 / 50000 h²-L85 / 50000 h³

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

R_g: 92²-98³, R_f: 86²-90³, R₍₁₋₁₅₎: 94²-88³

MR 0.53²-0.76³

MDER 0.48²-0.69³

Optical

High Performance Opal

PstLM ≤ 1.0 ⁴

SVM ≤ 0.4 ⁴

Flood

beam angle 30°

Electrical

DALI-2

2.7²-17.6³ W

PC1 220-240V

64²-109³ lm/W

1 DALI Addr.

29 W/m

Physical

length 710 mm

width 40 mm

height 100 mm

right

¹ RAL code ² Spot ³ Linear
⁴ Value of containing product at full load (undimmed)

Installation instructions

