

# TASK direct / indirect power

free standing U-shape

059-2942156Z



Project / Type	
Notes	
Count / Date	



## General

Floor , Standing	
grey , RAL9006 <sup>1</sup>	
IP20	
indirect 7800 lm	
direct 2550 lm	
total 10350 lm	

## LED

4000 K	
CRI ≥ 90	
L90 / 50000 h	
photobio. safety RG 0 - no Risk	
initial MacAdam ≤ 3 SDCM	
R <sub>g</sub> : 96 , R <sub>r</sub> : 90 , R <sub>t(1-5)</sub> : 87	
MR 0.75	
MDER 0.68	

## Optical

Microprismatic	
UGR < 13 , ≥65° <3000 cd/m <sup>2</sup>	
PstLM ≤ 1.0 <sup>2</sup>	
SVM ≤ 0.4 <sup>2</sup>	

## Electrical

touch DIM on pole	
80 W	
PC1 220-240V	
129 lm/W	

## Physical

U-shape	
length 800 mm	
width 320 mm	
height 1920 mm	
13.1 kg	


<sup>1</sup> RAL code <sup>2</sup> Value of containing product at full load (undimmed)

## Installation instructions



Free standing luminaire with rectangular head with rounded edges in aluminium; extremely flat design (only 15mm); rectangular aluminium tube support; base stand with recess for table stand (U-shape); modern shape in elegant design for discerning requirements; surface grey powder coated; direct light distribution through LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; microprismatic PMMA cover; completely homogeneous illumination; UGR ≤ 13; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m<sup>2</sup>; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; including TOUCH DIM control for individual control of the brightness; incl. connection cable (3m) with safety plug; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

## Light distribution



## Product drawing

