

TASK sensor direct / indirect power

free standing U-shape
059-2942078Z



Project / Type _____


Notes _____

Count / Date _____




Free standing luminaire with rectangular head with rounded edges in aluminium; extremely flat design (only 15mm); rectangular aluminium tube support; base stand with recess for table stand (U-shape); modern shape in elegant design for discerning requirements; surface black powder coated; direct light distribution through LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; microprismatic PMMA cover; completely homogeneous illumination; $UGR \leq 13$; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above $65^\circ \leq 3000 \text{ cd/m}^2$; light colour 3000 K; binning initial MacAdam $\leq 3 \text{ SDCM}$; $CRI \geq 90$; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; luminaire with integrated infrared presence and brightness sensor (ESSENTIAL sensor); automatic light control for individually adjustable brightness; variable automatic shutdown; including TOUCH DIM control for individual control of the brightness; presence sensor detection range $\phi 4,5\text{m}$ on the floor; incl. connection cable (3m) with safety plug; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Floor , Standing _____

black , RAL9005 ¹ _____

IP20 _____

indirect 7330 lm _____

direct 2400 lm _____

total 9730 lm _____

LED

3000 K _____

$CRI \geq 90$ _____

L90 / 50000 h _____

photobio. safety RG 0 - no Risk _____

initial MacAdam $\leq 3 \text{ SDCM}$ _____

$R_g: 96 , R_r: 90 , R_{t-15}: 90$ _____

MR 0.61 _____

MDER 0.56 _____

Optical

Microprismatic _____

$UGR < 13 , \geq 65^\circ < 3000 \text{ cd/m}^2$ _____

$P_{stLM} \leq 1.0^2$ _____

$SVM \leq 0.4^2$ _____

Electrical

ESSENTIAL sensor (brightness & presence) _____

80 W _____

PC1 220-240V _____

122 lm/W _____

Physical

U-shape _____

length 800 mm _____

width 320 mm _____

height 1920 mm _____

13.5 kg _____

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions

