

LINEA opal / asymmetric

wall

058-6172637AA



Project / Type

Notes

Count / Date



General

Wall , Surface

white , RAL 9010 ¹

IP20

indirect 1160 lm

direct 972 lm

total 2132 lm

3520 lm/m

LED

4000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 98 , R_r: 90 , R_{t(1-5)}: 88

MR 0.76

MDER 0.69

Optical

High Performance Opal / Asymmetric

asymmetric

P_{stLM} ≤ 1.0^{2 3}

SVM ≤ 0.4^{2 3}

Electrical

DALI-2

220-240 V

system 17.6 W

system 121 lm/W⁴

PC1

1 DALI Addr.

29 W/m

Physical

length 610 mm


width 40 mm

height 100 mm

1.7 kg

Light fitting and front cover made of extruded aluminium profile; angular design; no visible screws; surface white powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct light component: HPO (High Performance Opal) cover for uniform illumination; indirect light component: with specially computed, asymmetrical lens for homogeneous lighting intensity (installation optionally for floor or ceiling illumination); light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



¹ RAL code ² Linear

³ Value of containing product at full load (undimmed)

⁴ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

