

LINEA opal / opal

wall

058-6174637AH



Project / Type

Notes

Count / Date



General

Wall , Surface

white , RAL9010 ¹

3230 lm/m

IP20

indirect 1940 lm

direct 1940 lm

total 3880 lm

LED

4000 K

CRI ≥ 90

L85 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

R_g: 98 , R_r: 90 , R_{t[1-15]}: 88

MR 0.76

MDER 0.69

Optical


High Performance Opal

P_{stLM} ≤ 1.0 ²

SVM ≤ 0.4 ²

Light fitting and front cover made of extruded aluminium profile; angular design; no visible screws; surface white powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct and indirect light component: HPO (High Performance Opal) cover for uniform illumination; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



Electrical

DALI-2

35 W

PC1 220-240V

111 lm/W

1 DALI Addr.

29 W/m

Physical

length 1210 mm

width 40 mm

height 100 mm

2.81 kg

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions

