

TASK direct / indirect power

free standing U-shape

059-2942056Z




Project / Type	
Notes	
Count / Date	




Free standing luminaire with rectangular head with rounded edges in aluminium; extremely flat design (only 15mm); rectangular aluminium tube support; base stand with recess for table stand (U-shape); modern shape in elegant design for discerning requirements; surface grey powder coated; direct light distribution through LGP body (Light Guiding Prism); side coupled light directed downwards by laser engraving; indirect light component with special PCBs for increased luminous flux and maximum ceiling illumination; microprismatic PMMA cover; completely homogeneous illumination; UGR ≤ 13 ; VDU compatible workplace luminaire according to DIN EN 12464-1; luminance above 65° ≤ 3000 cd/m²; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; including TOUCH DIM control for individual control of the brightness; incl. connection cable (3m) with safety plug; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Floor Standing	
grey RAL 9006 ¹	
IP20	
indirect 7330 lm direct 2400 lm	
total 9730 lm	

LED

3000 K	
CRI ≥ 90	
L90 / 50000 h	
initial MacAdam ≤ 3 SDCM	
R _g : 96 R _f : 90 R _{t1-15} : 89	
MR 0.61 MDER 0.56	

Optical

Microprismatic microprismatic	
UGR ≤ 13 $\geq 65^\circ$ < 3000 cd/m ²	
PstLM ≤ 1.0 ² SVM ≤ 0.4 ²	

Electrical

touch DIM on pole	
PC1 220-240 V	
system 80 W	
system 122 lm/W ³	

Physical

U-shape	
length 800 mm width 320 mm height 1920 mm	
12.3 kg	

¹ RAL code ² Value of containing product at full load (undimmed)
³ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

