

LINEA opal / 1 spot

wall

058-6174548CH



Project / Type _____


Notes _____

Count / Date _____



Light fitting and front cover made of extruded aluminium profile; angular design; no visible screws; surface black powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct and indirect light component: HPO (High Performance Opal) cover for uniform illumination; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; JUST 26 spotlight module 2,2 W / 141 lm / 3000 K right, incl. switch; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;


Light distribution



flood 23° Spot

h (m)	E0° (lx)	ø (m)
1	584	0.41
2	146	0.83
3	65	1.24
4	37	1.65
5	23	2.07

Product drawing



General

Wall , Surface
black , RAL9005 ¹
2890 lm/m
IP20
indirect 1720 lm
direct 1760 lm
total 3480 lm
tilt max 89°
141 lm

LED

3000 K
CRI ≥ 90
L80 / 50000 h²-L85 / 50000 h³
photobio. safety RG 0 - no Risk
initial MacAdam ≤ 3 SDCM
R_g: 99 , R_r: 91 , R_{t(1-15)}: 89
MR 0.61
MDER 0.55

Optical

High Performance Opal
PstLM ≤ 1.0 ⁴
SVM ≤ 0.4 ⁴
Flood
beam angle 23°

Electrical

DALI-2 / switch (only spotlights)
2.2²-35³ W
PC1 220-240V
64²-99³ lm/W
1 DALI Addr.
29 W/m

Physical

length 1310 mm
width 40 mm
height 100 mm
right

¹ RAL code ² Spot ³ Linear
⁴ Value of containing product at full load (undimmed)

Installation instructions

