

LINEA opal / opal

wall system


058-6148D38AH



Project / Type


Notes

Count / Date




Light fitting and front cover made of extruded aluminium profile; angular design; linear; for lighting systems; no visible screws; surface black powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct and indirect light component: HPO (High Performance Opal) cover for uniform illumination; light colour: tunable white diodes (2700-5000 K); binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; incl. DALI-2 / DT8 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Wall | Surface

black | RAL 9005¹

IP20

indirect 4030 lm | direct 4030 lm

total 8060 lm

3350 lm/m

LED

tunable white | 2700 K - 5000 K

CRI ≥ 90

L85 / 50000 h

initial MacAdam ≤ 3 SDCM

R_g: 99 | R_f: 90 | R_{f(1-15)}: 88

MR 0.53 | MDER 0.48

Optical

High Performance Opal | opal (lambertsch)

PstLM $\leq 1.0^{2,3}$ | SVM $\leq 0.4^{2,3}$

Electrical

DALI-2 DT8 | 1 DALI Addr.

PC1 | 220-240 V

system 83 W

system 97 lm/W⁴

35 W/m

Physical

length 2406 mm | width 40 mm | height 100 mm

¹ RAL code ² Linear
³ Value of containing product at full load (undimmed)
⁴ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



LINEA opal / opal

wall system

058-6148D38AH



| | |
|----------------|--|
| Project / Type | |
| Notes | |
| Count / Date | |

Maintenance Factors

| Operating Time [h] | 10 000 | 20 000 | 30 000 | 40 000 | 50 000 |
|--------------------|------------------------------|--------|-------------------|---------------------------------|--------|
| LLMF | 0.98 | 0.96 | 0.94 | 0.91 | 0.89 |
| LSF | 1 | 1 | 1 | 1 | 1 |
| MF | LMF × RSMF × LLMF × LSF | | RSMF ^a | Room Surface Maintenance Factor | |
| MF | Maintenance Factor | | LLMF | Lamp Lumens Maintenance Factor | |
| LMF ^a | Luminaire Maintenance Factor | | LSF | Lamp Survival Factor | |

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

| Automatic Circuit Breaker Type | Number of Fixtures |
|--------------------------------|--------------------|
| B10 | 9 |
| B13 | 12 |
| B16 | 15 |
| B20 | 19 |
| C10 | 15 |
| C13 | 20 |
| C16 | 25 |
| C20 | 32 |

Mounting accessories

END CAPS

| TYPE | COLOUR | L-W-H (MM) | ARTICLE NUMBER(S) |
|--------|------------|------------|-------------------|
| 1 pair | pure white | 40-100-12 | 050-2540107 |
| 1 pair | jet black | 40-100-12 | 050-2540108 |



Mounting accessories

LINEAR CONNECTOR

| TYPE | ARTICLE NUMBER(S) |
|-----------|-------------------|
| 1 piece | 050-2551100 |
| 10 pieces | 050-2551100.10 |



Electrical accessories

THROUGH WIRE

| TYPE | ARTICLE NUMBER(S) |
|-----------|-------------------|
| 10 pieces | 004-90003 |
| 10 pieces | 004-90005 |

