

LINEA opal / opal

wall system

058-6148517AH



Project / Type _____


Notes _____

Count / Date _____



Light fitting and front cover made of extruded aluminium profile; angular design; linear; for lighting systems; no visible screws; surface white powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct and indirect light component: HPO (High Performance Opal) cover for uniform illumination; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 90 ; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; incl. converter, non dimmable; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Wall , Surface _____

white , RAL 9010 ¹ _____

IP20 _____

indirect 3520 lm _____

direct 3520 lm _____

total 7040 lm _____

2930 lm/m _____

LED

3000 K _____

CRI ≥ 90 _____

L85 / 50000 h _____

initial MacAdam ≤ 3 SDCM _____

R_g: 99 , R_r: 91 , R_{t(1-15)}: 89 _____

MR 0.61 _____

MDER 0.55 _____

Optical

High Performance Opal _____

opal (lambertsch) _____

P_{stLM} $\leq 1.0^2$ ³ _____

SVM $\leq 0.4^2$ ³ _____

Electrical

non DIM _____

220-240 V _____

system 71 W _____

system 99 lm/W⁴ _____

PC1 _____

29 W/m _____

Physical

length 2406 mm _____

width 40 mm _____

height 100 mm _____

5.4 kg _____

¹ RAL code ² Linear

³ Value of containing product at full load (undimmed)

⁴ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions

