

LINEA opal / opal

wall system

058-6144D37AH



Project / Type

Notes

Count / Date



General

Wall , Surface

white , RAL 9010 ¹

IP20

indirect 2020 lm

direct 2020 lm

total 4040 lm

3350 lm/m

LED

tunable white

2700 K - 5000 K

CRI \geq 90

L85 / 50000 h

initial MacAdam \leq 3 SDCM

R_g: 99 , R_r: 90 , R_{r[1-15]}: 88

MR 0.53

MDER 0.48

Optical

High Performance Opal

opal (lambertsch)

PstLM \leq 1.0² ³

SVM \leq 0.4² ³

Electrical

DALI-2 DT8

220-240 V

system 42 W

system 96 lm/W⁴

PC1

1 DALI Addr.

35 W/m

Physical

length 1206 mm

width 40 mm

height 100 mm

2.8 kg

¹ RAL code ² Linear

³ Value of containing product at full load (undimmed)


⁴ incl. consideration of optical losses, internal control unit losses & operating device efficiency

Installation instructions



Light fitting and front cover made of extruded aluminium profile; angular design; linear; for lighting systems; no visible screws; surface white powder coated; suitable for wall mounting; homogeneous wall or ceiling illumination through uniform direct/indirect light distribution; direct and indirect light component: HPO (High Performance Opal) cover for uniform illumination; light colour: tunable white diodes (2700-5000 K); binning initial MacAdam \leq 3 SDCM; CRI \geq 90; min. 85% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; degree of protection IP20; PC1; 220-240 V; incl. DALI-2 / DT8 converter; accessories are listed separately; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing

