

CANYON 60 high lumen

trim offset

052-52M8638H



Project / Type


Notes

Count / Date




Luminaire housing made of extruded aluminium profile; uncluttered ceiling look through recessed luminaire plane; recessed light with wrap around edge; suitable for ceiling thickness of 8-25 mm; surface black powder coated; lighting profile (end cover and mounting bracket pre-assembled) available in advance for installation; remaining lamp components mounted without tools; luminaire ball proof version to 57710 part 13 / VDE 0710 part 13; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 4000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; HPO (High Performance Opal) cover for uniform illumination; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. DALI-2 converter; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Recessed

black , RAL9005 ¹

1340 lm/m

IP20

Ball impact resistant DIN 18032-3

3150 lm

LED

4000 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.72

MDER 0.66

Optical

High Performance Opal

PstLM ≤ 1.0 ²

SVM ≤ 0.4 ²

Electrical

DALI-2

55 W

PC1 220-240V

57 lm/W

1 DALI Addr.

24 W/m

Physical

trim

length 2365 mm

width 78 mm

height 113 mm

6.5 kg

Cutout

length 2358 mm

width 70 mm

min. ceiling thickness 8 mm

max. ceiling thickness 25 mm

recessed depth 138 mm

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator

