

CANYON 60 high lumen

trim offset

052-52M8517Z




Project / Type
Notes
Count / Date




Luminaire housing made of extruded aluminium profile; uncluttered ceiling look through recessed luminaire plane; recessed light with wrap around edge; suitable for ceiling thickness of 8-25 mm; surface white powder coated; lighting profile (end cover and mounting bracket pre-assembled) available in advance for installation; remaining lamp components mounted without tools; luminaire ball proof version to 57710 part 13 / VDE 0710 part 13; LED light inset consisting of highly reflective lacquered aluminium for improved thermal management; light colour 3000 K; binning initial MacAdam ≤ 3 SDCM; CRI ≥ 80 ; min. 90% of luminous flux after 50000 operating hours; energy efficient LEDs with high CRI; micro prismatic PMMA diffuser incl. diffuser film for homogeneous illumination and reduced luminance; degree of protection IP20; PC1 220-240V; photobiological safety according to IEC 62471 risk group RG 0 - no Risk; internal wiring in light halogen free; incl. converter, non dimmable; light source replaceable by an authorized professional; control gear replaceable by an authorized professional;

Light distribution



Product drawing



General

Ceiling , Recessed
white , RAL9016 ¹
1960 lm/m
IP20
Ball impact resistant DIN 18032-3
4590 lm

LED

3000 K
CRI ≥ 80
L90 / 50000 h
photobio. safety RG 0 - no Risk
initial MacAdam ≤ 3 SDCM
MR 0.54
MDER 0.49

Optical

Microprismatic
PstLM ≤ 1.0 ²

Electrical

non DIM
55 W
PC1 220-240V
83 lm/W
24 W/m

Physical

trim
length 2365 mm
width 78 mm
height 113 mm
7 kg

Cutout

length 2358 mm
width 70 mm
min. ceiling thickness 8 mm
max. ceiling thickness 25 mm
recessed depth 138 mm

¹ RAL code ² Value of containing product at full load (undimmed)

Installation instructions



Lighting calculator



CANYON 60 high lumen

trim offset

052-52M8517Z



Project / Type

Notes

Count / Date

Maintenance Factors

Operating Time [h]	10 000	20 000	30 000	40 000	50 000
LLMF	0.98	0.95	0.93	0.91	0.9
LSF	1	1	1	1	1
MF	LMF × RSMF × LLMF × LSF		RSMF ^a	Room Surface Maintenance Factor	
MF	Maintenance Factor		LLMF	Lamp Lumens Maintenance Factor	
LMF ^a	Luminaire Maintenance Factor		LSF	Lamp Survival Faktor	

^a According to "CIE 97, Maintenance of indoor electric lighting systems", 2005, ISBN 3-900-734-34-8. The values must be determined by the planner.

Circuit Breaker Types

Automatic Circuit Breaker Type	Number of Fixtures
B10	15
B13	19
B16	24
B20	30
C10	25
C13	32
C16	40
C20	49

