

# LENO microprismatic

semi-recessed / surface system

051-8216637G 051-8920187



Project / Type

Notes

Count / Date



### General

Ceiling / Wall , Surface<sup>1</sup>-Semi-Recessed<sup>2</sup>  
white , RAL9010 <sup>3</sup>  
2010 lm/m  
front IP20<sup>1</sup>-IP40<sup>2</sup> , back IP20  
3680 lm

### LED

4000 K  
CRI ≥ 80  
L90 / 50000 h  
photobio. safety RG 0 - no Risk  
initial MacAdam ≤ 3 SDCM  
MR 0.72  
MDER 0.66

### Optical

Microprismatic  
UGR < 19  
PstLM ≤ 1.0 <sup>4</sup>  
SVM ≤ 0.4 <sup>4</sup>

### Electrical

DALI-2  
28.6 W  
PC1 220-240V  
129 lm/W  
1 DALI Addr.  
16 W/m


### Physical

length 1830 mm  
width 89 mm  
height 28 mm  
4.3 kg


### Cutout

length 1843 mm  
width 70 mm  
min. ceiling thickness 12.5 mm  
recessed depth 13 mm

### Light distribution



### Product drawing



<sup>1</sup> surface <sup>2</sup> semi-recessed <sup>3</sup> RAL code  
<sup>4</sup> Value of containing product at full load (undimmed)

### Installation instructions

