

# LENO jut-out

semi-recessed / surface system

051-8216537J 051-8920188



Project / Type

Notes

Count / Date



### General

Ceiling / Wall , Semi-Recessed<sup>1</sup>-Surface<sup>2</sup>

black , RAL9005 <sup>3</sup>

1930 lm/m

front IP40<sup>1</sup>-IP20<sup>2</sup> , back IP20

3520 lm

### LED

3000 K

CRI ≥ 80

L90 / 50000 h

photobio. safety RG 0 - no Risk

initial MacAdam ≤ 3 SDCM

MR 0.54

MDER 0.49

### Optical

Jut-Out

PstLM ≤ 1.0 <sup>4</sup>

SVM ≤ 0.4 <sup>4</sup>

### Electrical

DALI-2

28.6 W

PC1 220-240V

123 lm/W

1 DALI Addr.

16 W/m

### Physical


length 1830 mm

width 89 mm


height 38 mm

4.3 kg

### Light distribution



### Product drawing



### Cutout

length 1843 mm

width 70 mm

min. ceiling thickness 12.5 mm

recessed depth 13 mm

<sup>1</sup> semi-recessed <sup>2</sup> surface <sup>3</sup> RAL code  
<sup>4</sup> Value of containing product at full load (undimmed)

### Installation instructions

